MCO-173AIC-PE

IncuSafe

CO_2 Incubators 165 L

DIRECT HEAT system | IR dual sensor | inCu saFe | SafeCell LED UV (option*) | H_2O_2 decontamination (option**) | MDR Medical Device Regulation (page 2#) | LabSVIFT

Optimising cell culture outcomes and reproducibility

IncuSafe CO_2 Incubators provide precise control of CO_2 concentration and accurate, uniform, and highly responsive temperature control within the chamber. During cell culturing the inCu-saFe germicidal interior and SafeCell UV-LED lamp work continuously to prevent contamination.

Precise & Regulated Environment

InCu-saFe and SafeCell UV-LED both function to prevent contamination. The Direct Heat and Air Jacket System regulates the temperature whilst the Dual IR sensor controls the CO_2 level.

Time-Saving Decontamination

The high-speed decontamination system uses vaporised hydrogen peroxide. It cleans the chamber of the incubator safely in less than three hours, achieving a minimal 6 log reduction of major contaminants.

Ease of Use & Maintenance

A new 7 inch color LCD touch panel allows full control even with gloved hands. Transfer of data is easy via a USB port. The easy-to-clean incubator interior features fully rounded corners and integrated shelf supports.



Optimum Cell Growth
Outstanding quality and performance for successful cell growth, optimal results and reproducibility. Perfect fit for the strictest and most sensitive protocols.

Efficient Workflows
Complete laboratory procedures and experiments more efficiently with less incubator downtime. Ideal for commercial applications.

Intuitive Usability
Control and visibility of the internal conditions, such as CO_2 level and temperature, is easy with the MCO-173AIC CO_2 incubator.

* Standard for Models MCO-173AICUV-PE/MCO-173AICUVH-PE
** Standard for Model MCO-173AICUVH-PE

IncuSafe CO_2 Incubators

Direct Heat and Air Jacket System

Achieves accurate, uniform, and highly responsive temperature control within the chamber, providing exceptional uniformity and rapid recovery after door-openings.

Dual IR CO_2 Sensor

The incubator's Dual IR sensor and P.I.D control enables ultra-fast CO_2 recovery without overshoot, even following multiple door-openings.

Active Background Decontamination

The exclusive inCu-saFe copper-enriched stainless steel alloy interor offers the germicidal properties of copper and the durability of stainless steel. The optional, isolated, SafeCell UV -LED lamp decontaminates water in the humidifying pan, without harming cultured cells.

Condensation Management

The 'dew stick'-controlled by Peltier technology-condenses water on its surface, which then drips into the humidifying pan, preventing unwanted condensation in the chamber and possible contamination.

Dimensions



Unit: mm (inch)

#)

CE 0123 **Available in these countries as Class IIa Medical Device:**
Austria, Belgium, Cyprus, France, Germany, Ireland, Italy, Liechtenstein, Luxemburg, Malta, the Netherlands, Poland, Spain, Switzerland and the United Kingdom.

CE **Available as equipment for laboratory use in:**
EEA countries, Switzerland, the United Kingdom and Turkey.

Model Number		MCO-173AIC-PE	MCO-173AICUV-PE	MCO-173AICUVH-PE
External Dimensions (W x D x H)[1]	mm	620 x 730 x 905		
Internal Dimensions (W x D x H)	mm	490 x 523 x 665		
Volume	liters	165		
Net Weight	kg	69		
Performance				
Temperature Control Range & Fluctuation	°C	AT +5 ~ +50, ±0.1		
Temperature Uniformity[2]	°C	±0.25		
CO_2 Control Range & Fluctuation	%	0 ~ 20, ±0.15		
Humidity Level & Fluctuation	%RH	95, ±5		
H_2O_2 Decontamination		Optional	Optional	Standard
Control				
Temperature Sensor		Thermistor		
CO_2 Sensor		Dual IR		
Display		WVGA full color LCD touchpanel		
Construction				
Exterior Material		Painted Steel (rear cover not painted)		
Interior Material		Stainless Steel Copper-Enriched Alloy		
Insulation Material		Expandable styrene-acrylonitrile beads		
Heating Method		Direct Heat & Air Jacket System		
Outer Door	qty	1		
Electric Door lock with Password		Optional	Optional	Standard
Field Reversible Door		Included		
Inner Door	qty	1 gas tight - made of tempered glass		
Shelves	qty	4 x Stainless Steel Copper-enriched Alloy		
Shelf Dimensions (W x D x H)	mm	470 x 450 x 12		
Max. Load per Shelf	kg	7		
Max. Shelf Capacity	qty	10		
Access Port	qty	1		
Access Port Position		Rear Upper Left		
Access Port Diameter	Ø mm	30		
Alarms		(R = Remote Alarm, V = Visual Alarm, B = Buzzer Alarm)		
Power Failure		V-B-R		
Out of Temperature Setting		V-B-R		
High Temperature		V-B-R		
Out of CO_2 Setting		V-B-R		
Door open		V-B		
Electrical and Noise Level				
Power Supply	V	230		
Frequency	Hz	50		
Noise Level[3]	dB	29		
Options				
Electrical Door Lock With Password		MCO-170EL-PW		Standard
SafeCell UV-LED® System		MCO-LUVS-PW[4]	Standard	
H_2O_2 Decontamination Board		MCO-HK-PW[4]		Standard
H_2O_2 Vapor Generator		MCO-50HP-PW[4]		
H_2O_2 Reagent, pack of 6 bottles		MCO-20H2O2-PE		
CO_2 Gas Pressure Regulator		MCO-010R-PW		
Automatic CO_2 Cylinder Changeover System		MCO-21GCP-PW		
Semi-automatic one point Gas Calibration Kit		MCO-SG-PW		
InCu-saFe® Shelf		MCO-170ST-PW		
InCu-saFe® Half Tray System		MCO-25ST-PW		
Double Stacking Bracket*		MCO-170PS-PW		
Stacking Plate*		MCO-170SB-PW		
Roller Base		MCO-170RB-PW		
Communication systems [5]				
Analogue interface (4-20mA)		Standard		
Mod-bus interface board		MTR-MODB1-PW		
OPC-UA interface board		MTR-OPC1-PW		

Appearance and specifications are subject to change without notice.

[1] Exterior dimensions of main cabinet only, excluding handle and other external projections.
[2] ±0.25°C; ambient temp 23°C - 25°C, setting 37°C, CO_2 5%, no load
[3] Nominal value
[4] MCO-173AIC-PE requires MCO-HK-PW, MCO-50HP-PW and SafeCell UV-LED option for H_2O_2 decontamination
[5] Can only be fitted with one communications interface.

* If stacking two incubators, make sure the double-stacking dedicated securing hardware and spacer are used.

PHC Europe
A Member of PHC Group

Eikdonk 1 | 4825 AZ Breda | Netherlands
T: +31 (0) 76 543 3833
www.phchd.com/eu/biomedical

Version: 280826